

Technical Data Sheet



ORF Acrylic Primer

Page 1 of 1

Date: 01 – 11 - 22

Application

- ORF Acrylic Primer is a single component primer used for sealing and priming.
- ORF Acrylic Primer is a primer to be used on concrete and asphalt substates, which is suitable for all ORF Acrylic Flooring systems.

Properties

- ORF Acrylic Primer has good sealing properties, Excellent foundation for ORF Acrylic Resurfacer.
- Good adhesive strength Quick drying Moisture vapor permeable.

Packaging & Colours

- ORF Acrylic Primer is available in 18 kg drum.
- Colour: White

Storage

- Store in original containers, under dry conditions.
- Do not expose to direct sunlight. Protect from frost.
- Shelf Life Approx. 6 Months if stored correctly.

Our recommendations concerning the technical application of the product, whether through oral or written communication or through demonstration, are given to the best of our current knowledge; however, any such instruction shall be without commitment, including where any protective rights of third parties are involved. They do not free you of the obligation to check the products supplied by us for their suitability for the procedures and applications envisaged. The (intended) use and application of the products are beyond our control. They are therefore your personal responsibility. In the event that ORF proves liable, such liability shall be limited in all cases of damage to a sum not exceeding the actual value of the goods supplied by us and used by you. It goes without saying that we guarantee the good quality of our products, in accordance with the standards set out in our

General Terms of Sale and Delivery.