

Technical Data Sheet



ORF Acrylic Resurfacer

Page 1 of 1
Date: 01 – 11 - 22

Application

- ORF Acrylic Resurfacer is a water based heavy –bodied binder.
- ORF Acrylic Resurfacer is intended to use for Tennis courts, Basketball courts Volleyball courts and other Multipurpose sports flooring.
- Surface should be cleaned from dust, dirt, oil, and all other loose materials before the application of ORF Acrylic Resurfacer.
- It's recommended to apply two coats of ORF Acrylic Resurfacer in order to have a good surface for the application of ORF Acrylic Basecoat.

Properties

- Excellent construction performance.
- High strength, greatly extend the life of the stadium.
- Good Flatness, excellent repair base defects.
- High level of motion quality.
- Excellent weather resistance.
- Abrasion-resistance.

Packaging & Colours

- ORF Acrylic Resurfacer is available in 210 kg drum.
- Colours availability: Grey and Black.

Mixing

- 1 kg. of ORF Acrylic Resurfacer + 2 kg. silica sand (500 microns).
- Add water until the correct consistency is achieved.

Storage

- Store in original containers, under dry conditions.
- Do not expose to direct sunlight. Protect from frost.
- Shelf Life Approx. 6 Months if stored correctly.

Our recommendations concerning the technical application of the product, whether through oral or written communication or through demonstration, are given to the best of our current knowledge; however, any such instruction shall be without commitment, including where any protective rights of third parties are involved. They do not free you of the obligation to check the products supplied by us for their suitability for the procedures and applications envisaged. The (intended) use and application of the products are beyond our control. They are therefore your personal responsibility. In the event that ORF proves liable, such liability shall be limited in all cases of damage to a sum not exceeding the actual value of the goods supplied by us and used by you. It goes without saying that we guarantee the good quality of our products, in accordance with the standards set out in our

General Terms of Sale and Delivery.